


Smooth low end, smooth mid range, good high end response. Great for combos, 1& 2x12 and lead guitar.

Giving an unbelievable thick warm tone with an immense push that remains detailed.

## FREQUENCY RESPONSE DATA\*



## ELECTRO ACQUETIO EDECIFICATIONE

ELLUTTIO ACCOUNTIC	JI LUII IUATIUNS
Nominal Chassis Diameter	12"
Impedance	4/8/16Ω
Power Handling	150 w (AES)
Sensitivity (1 w - 1 m)	103 dB
Chassis Type	Pressed Steel
Voice Coil Diameter	2.0" / 50.8 mm
Coil Material	Copper
Magnet Type	Ferrite
Magnet Weight	50 oz
Usable Frequency Range	80 Hz - 6.2 kHz
Resonance FS Hz	84
RE Ohms	6.3 Ω

## MOUNTING / SHIPPING INFORMATION

Overall Diameter	12.20" / 310 mm
Overall Height	5.11" / 130 mm
Magnet Diameter	6.10" / 155 mm
Baffle Hole F/M	11.25" / 286 mm
Mounting Hole Qty and Diameter	8x 7.0 mm
ixing Holes	11.75" / 298 mm PCD
Nett Weight	9.02 lb / 4.15 kg
Shipping Weight	10.8 lb / 4.8 kg
Packing Carton Dimensions	340 x 340 x 222 mm