



NA1394-6-W-B

Firewire 6 with IEEE 1394 6 pole receptacles on both ends, black D-housing

Due to the rising digitisation the interface problems between audio/video networks, IT equipment (e.g. Mac) and mLAN connections increase.

Neutrik's Firewire feedthrough type 1394a, mounted in the standardized D-shape housing, solves this problem.

Features & Benefits

- Ideal for audio networking and integration of digital equipment into audio systems
- Universally accepted standard D-shape housing
- Firewire feedthrough with 6 pole IEEE 1394 receptacle at both ends
- Removable screen to chassis grounding:

Technical Information

| Product | |
|------------------------|--------------|
| Title | NA1394-6-W-B |
| Connection Type | Firewire |
| Gender | female |

| Mechanical | |
|---------------------------|----------------|
| Wiresize | |
| Mounting direction | Front mounting |
| Chassis shape | D |

| Material | |
|------------------------|-------------------------|
| Contact plating | Au |
| Contacts | Brass (CuZn39Pb3) |
| Insert | PBTP 15 % GR |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Black chromium |

| Environmental | |
|----------------------------|------------------|
| Flammability | UL 94 V-0 |
| Standard compliance | IEEE 1394 |
| Temperature range | -25 °C to +85 °C |