

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® C128 L.S.Z.H. – 2x0,35 mm<sup>2</sup>

**Firestop®** Low Capacity Balanced Microphone Cable **Halogen Free**



**CATEGORY** Balanced Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Premade Cables and Microphones.

- A:** Soft **L.S.Z.H.** Sheath – Flame Retardant and Halogen Free. OUTDOOR LIMITED. Outer cable Diam. Ø 6,30 (±0,20) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 90%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Transparent Cores Insulation with compact PE. Diam. Ø 1,70 (±0,20) mm.
- E:** One conductor in O.F.C. red copper and one in O.F.C. tinned copper formation 11x0,20 mm. Nom. Cross section 2x0,35 mm<sup>2</sup>.

**MARKING** tasker® C128 L.S.Z.H. 2x0,35 mm<sup>2</sup> O.F.C. Low Capacitance Supreme Microphone Cable – Halogen Free - Firestop® Made in Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **PVC, PE, PUR**, with or without Metallic Armor.

### Cable Properties

|                              |           |
|------------------------------|-----------|
| <b>Conductor Resistance</b>  | 58 Ω/Km   |
| <b>Capacity Core/Core</b>    | 55 pF/mt  |
| <b>Capacity Core/Shield</b>  | 92 pF/mt  |
| <b>Max Rated Voltage</b>     | 49 V      |
| <b>Operative Temperature</b> | -30/+70°C |

|                |          |                       |                   |                     |          |                      |                  |                     |          |                   |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|------------------|---------------------|----------|-------------------|
| <b>USE</b>     | <b>X</b> | Indoor                | Interno Edificio  | <b>INSTALLATION</b> | <b>X</b> | Fixed                | Fissa            | <b>INFORMATION</b>  | <b>X</b> | RoHS2 Compliant   |
| <b>Impiego</b> | <b>X</b> | Outdoor Limited       | Esterno Limitato  | <b>Posa</b>         | <b>X</b> | Restricted Mobile    | Mobile Limitata  | <b>Informazioni</b> | <b>X</b> | Ver. A / 16.05.16 |
|                |          | Outdoor               | Esterno           |                     |          | Mobile               | Mobile           |                     |          |                   |
|                |          | Outdoor Direct Burial | Esterno Interrato |                     |          | Mobile in Drag Chain | Mobile in Catena |                     |          |                   |